


# Parabolic antenna JRC-24



diagrams



[Mounting instruction](#)

Variations:

- **JRC-24**
- **[JRC-24 EXTREM](#)**

Usage:

- excellent parabolic antenna for demanding users
- direction links for medium and long distance, also short in difficult conditions
- client antenna for larger distances or for difficult conditions
- outdoor usage
- all-metal construction, parabola made of aluminium alloy
- holder is prepared for instalation of [GentleBOX JR-200](#), the connector leads into it directly
- setting elevation (of gradient) and azimuth has independent adjustment
- VSWR is measured during the manufacture of **every piece**
- **radom** (plastic parabola cover) **for each antenna free!**

Technical parameters

<b>Frequency range</b>	5,0 - 5,95 GHz
<b>Gain</b>	22 dBi <sub>5,2 GHz</sub> 23,5 dBi <sub>5,8 GHz</sub>
<b>VSWR</b> <sub>5,35-5,95 GHz</sub>	≤ 1,5
<b>Front to back ratio</b>	≥ 30 dB
<b>Beamwidth</b> <sub>-3 dB</sub>	8,8°
<b>Connector</b>	N - Female
<b>Polarization</b>	horizontal or vertical according to radiator position
<b>Parabola</b>	aluminium alloy with baking colour ø 38 cm
<b>Cover</b>	UV steady plastic ABS

The radiator is internally treated by high frequency technology "**Hydrophobic coating**" which increases resistance against humidity.

Recommended accessories:

- [GentleBOX JR-200](#)
- [Antenna bracket KNS2](#)

Packing

- 2 pcs in carton
- Size and EAN codes [more](#)

More foto

