


Dual-polarized parabolic antenna JRC-29 DuplEX



diagrams



[Mounting instruction](#)

Variations:

- **JRC-29 DuplEX**
- [JRC-29](#)
- [JRC-29 EXTREM](#)

Usage:

- dual-polarized antenna, horizontal and vertical polarization
- **the highest isolation! 53 dB**
- only **1 antenna instead 2 save money** for mast!
- extra high front to back ratio
- metallic collar assures increased isolation between antenna on mast = lower interference between links
- direction links for long and medium distance, also short in difficult conditions
- setting elevation (of gradient) and azimuth has independent adjustment
- VSWR and isolation are measured during the manufacture of **every piece**
- outdoor usage
- **radom** (plastic parabola cover) **for each antenna free!**

Technical parameters

Frequency range	5,45 - 5,9 GHz
Gain	28,6 ±0,6dBi
VSWR	≤ 1,5
Isolation between connectors	53dB (≥45dB)
Front to back ratio	≥ 43 dB
Beamwidth_{3 dB}	5,8°
Connector	N - Female
Polarization	linear, horizontal and vertical
Parabola	∅ 65 cm
Cover	aluminium alloy with baking colour UV steady plastic ABS

The radiator is internally treated by high frequency technology "**Hydrophobic coating**" which increases resistance against humidity.

Facilities for application:

- duplex direction link
- 2 independent links
- **we prepare more application informations**

Packing

- 2 pcs in carton
- Size and EAN codes [more](#)

More foto

