


Parabolic antenna JRC-29 EXTREM



diagrams



[Mounting instruction](#)

Variations:

- [JRC-29](#)
- **JRC-29 EXTREM**

Usage:

- excellent parabolic antenna for demanding users for very difficult conditions
- direction links for medium and long distance for safety connection
- extra high front to back ratio
- metallic collar assures increased isolation between antenna on mast = lower interference between links
- increased resistance against interference from sides and behind
- all-metal construction, parabola made of aluminium alloy
- holder is prepared for installation of [GentleBOX JR-200](#), the connector leads into it directly
- setting elevation (of gradient) and azimuth has independent adjustment
- exact and comfortable adjustment of elevation by setting screw
- VSWR is measured during the manufacture of **every piece**
- outdoor usage
- **radom** (plastic parabola cover) **for each antenna free!**

Technical parameters

Frequency range	5,0 - 5,95 GHz
Gain	28,4 ± 0,5 dBi
VSWR <small>5,45-5,85 GHz</small>	≤ 1,5
Beamwidth <small>3 dB</small>	5,8°
Connector	N - Female
Polarization	horizontal or vertical according to radiator position
Parabola	∅ 65 cm
Cover	aluminium alloy with baking colour
	UV steady plastic ABS

The radiator is internally treated by high frequency technology "**Hydrophobic coating**" which increases resistance against humidity.

Recommended accessories:

- [GentleBOX JR-200](#)

Packing

- 2 pcs in carton
- Size and EAN codes [more](#)

More foto

